(54) **TERMINAL DEVICE, BASE STATION APPARATUS, AND COMMUNICATION METHOD**

(71) Applicant: **SHARP KABUSHIKI KAISHA**, Sakai City, Osaka (JP)

(72) Inventors: **Toshizo NOGAMI**, Sakai City (JP); **Kazuyuki SHIMEZAWA**, Sakai City (JP); **Wataru OUCHI**, Sakai City (JP); **Naoki KUSASHIMA**, Sakai City (JP); **Alvaro RUIZ DELGADO**, Sakai City (JP)

(73) Assignee: **SHARP KABUSHIKI KAISHA**, Sakai City, Osaka (JP)

(57) **ABSTRACT**

A power for a physical uplink channel is determined based on whether or not P_{CMAX} that is a maximum transmit power for a terminal device is exceeded, in a case where dual connectivity is not configured for the physical uplink channel, and a power for the physical uplink channel in a first cell group is determined based on whether or not P_{MCG} that is a maximum transmit power for the first cell group is exceeded, a power for the physical uplink channel in a second cell group is determined based on whether or not P_{SCG} that is a maximum transmit power for the second cell group is exceeded, P_{MCG} is calculated by an arithmetic operation that uses at least P_{CMAX} and P_{SeNB}, and P_{SCG} is calculated by an arithmetic operation that uses at least P_{CMAX} and P_{MeNB}, in a case where the dual connectivity is configured for the physical uplink channel.